

DESCRIPTION

PRINTED MATTER, ITS APPLICATION AND ITS PRODUCTION METHOD

5

TECHNICAL FIELD

The present invention relates to a printed matter having fixed information printed in a conventional printing method and having a receiving layer for an ink jet recording ink for printing variable information wherein a beautiful image having both fixed information and variable information can be formed efficiently thereon. The invention relates also to a printed matter having variable information printed in the receiving layer by an ink jet recording method and to a method for its production.

15

BACKGROUND ART

The ink jet recording method utilizes piezo electric elements, thermal energy, electrical attraction force or the like as a method for spouting an ink. Even when any of the methods is used, this recording method does not need large-scale equipment. Moreover, the recording method has a feature that the images captured with personal computers or the like can be printed directly in any desired receptor. Therefore, this recording method is spreading quickly as a method that can print color image information easily. However, very expensive exclusive paper is required in order to obtain beautiful printed matters since blurring or muddying occurs when printed on plain paper. The ink jet recording method can print only at a slow speed and the ink itself is expensive. For these reasons, the ink jet recording method is

unsuitable for producing a large number of prints.

On the other hand, since a printing method using a printing ink (conventional printing method) can produce clear printed matters at a high speed using ink and printing paper of low cost, it is suitable for producing a large number of prints at once. However, in the case where different images are printed each in a small amount, since plates whose number is equal to that of the images are required, the cost of platemaking and the time for plate exchanging work increase, resulting in an increase in economical burden and loss of time.

These days, a method for producing efficiently large quantities of printed matters having variable information has been developed by taking advantage of the handiness of the ink jet recording method and the high speed performance of the conventional printing method. This is a method in which an image of fixed information is printed in a large number of prints by the usual printing method and variable information is printed afterwards in the required numbers of prints by the ink jet recording method. This method can produce printed matters having both fixed information and variable information far economically and far efficiently than the case where all information is printed by one of the methods.

However, as mentioned above, the attempt to obtain a beautiful image by the current ink jet recording method requires expensive exclusive papers. There is a problem that most of such exclusive papers are not suitable for the conventional printing method and cannot be used as they are.

Furthermore, as disclosed in JP, A, 8-230307 and the like, there is also a problem that a water-based ink for ink jet recording is

repelled on the printed surface obtained by using offset printing ink (oil-based ink), resulting in failure to form any image.

The information to be printed afterwards by the ink jet recording method is restricted to mainly a simple text such as a lot
5 number and production date of the content and the use-by date in food products applications, which is not satisfactory in the field where the beauty of patterns or the like is required.

However, recently, in leaflets of supermarkets or volume
10 retailers of chain systems, there is increasing demand for printed matters wherein fixed image information such as pictures of articles to be commonly sold in all the chain stores is printed by the usual printing method and afterwards pictures of articles for special sale different between every chain stores or designed image information of even letters such as prices are printed by the ink jet recording method. Therefore,
15 even in the ink jet recording, an image quality comparable to that of the conventional printing has been required.

For example, JP, A, 11-78219 or the like discloses coated paper that has receivability to both a printing ink and an ink jet recording ink and an attempt to make quality of image equal with both of
20 the inks is also performed.

However, there is an economical disadvantage problem with this method because of the necessity to apply an expensive coating composition comprising special materials onto the entire surface of paper. Furthermore, there still remains a problem that since an ink jet
25 recording ink is repelled by a surface printed with an oil-based ink, the oil-based ink cannot be printed in the area where variable information will be printed afterwards and therefore the design is limited.

Thus, today, the use of the both methods, the conventional printing and the ink jet recording, can increase the production efficiency of printed matters having variable information, but it is not possible to form beautiful images economically by the both methods.

5 An object of the present invention is to solve the above problems and to provide printed matters having beautiful images which have both fixed information and variable information printed by both the conventional printing method and the ink jet recording method with excellent efficiency and also economy.

10 DISCLOSURE OF INVENTION

That is, the present invention provides the following printed matters, applications thereof and production methods thereof.

15 (1) A printed matter having a receiving layer for an ink jet recording ink for printing variable information formed on the entire or a part of the surface of a printing paper having fixed information printed by using a printing method selected from lithographic printing, relief printing and intaglio printing.

20 (2) The printed matter according to item (1), wherein the receiving layer for an ink jet recording ink comprises at least two layers containing different ingredients respectively, at least one layer of them being a receiving layer comprising an ink-absorbing resin as its main ingredient and at least the other layer of them being a receiving layer comprising an ink-fixing resin as its main ingredient.

25 (3) The printed matter according to item (2), wherein the receiving layer comprising an ink-absorbing resin as its main ingredient is a receiving layer for an ink jet recording ink containing at least one

ink-absorbing resin selected from the group consisting of proteins, starches, celluloses, polyvinyl alcohols, polyvinyl acetals and polyvinylpyrrolidones.

(4) The printed matter according to item (2) or item (3),
5 wherein the receiving layer comprising an ink-absorbing resin as its main ingredient is a receiving layer for an ink jet recording ink further containing a filler.


(5) The printed matter according to item (2) or item (3),
wherein the receiving layer comprising an ink-fixing resin as its main
10 ingredient is a receiving layer for an ink jet recording ink containing at least one ink-fixing resin selected from the group consisting of resins having a cationic group in their molecules.

(6) The printed matter according to any one of items (1) to (5),
wherein the receiving layer is formed at least on the print film of the ink
15 used for printing the fixed information.

(7) The printed matter according to item (6), wherein the fixed
information is printed with an oil-based ink by using the lithographic
printing method or the relief printing method, and the receiving layer for
an ink jet recording ink is formed at least on the print film of the oil-
20 based ink, the receiving layer comprising one layer or two or more layers containing different ingredients, wherein the layer adjoining the print film of the oil-based ink contains a film-forming acrylic resin obtained by emulsion polymerizing monomers containing 15% by weight or more of a (meth)acrylic ester compound containing an alkyl group having 8 to 18
25 carbon atoms.

(8) The printed matter according to item (6) or item (7),
wherein the fixed information is printed with an oil-based ink by using

the lithographic printing method or the relief printing method, and the receiving layer for an ink jet recording ink is formed at least on the print film of the oil-based ink, the receiving layer comprising one layer or two or more layers containing different ingredients, wherein the layer adjoining the print film of the oil-based ink is formed from a coating agent further containing 1 to 8% by weight of at least one film forming-improving agent selected from the group consisting of the compounds represented by the following general formulas (1) to (3):



wherein X^1 denotes an alkylene group having 2 to 4 carbon atoms, Y^1 and Z^1 each denote an alkyl group having 1 to 4 carbon atoms, n denotes an integer of 1 to 4; X^2 denotes an alkylene group having 2 to 8 carbon atoms, Y^2 denotes H or an alkyl group having 1 to 11 carbon atoms, Z^2 denotes an alkyl group having 4 to 11 carbon atoms or an acyl group having 4 to 11 carbon atoms with the proviso that Y^2 is H, Z^2 denotes an acyl group having 4 to 11 carbon atoms with the proviso that Y^2 is an alkyl group having 1 to 3 carbon atoms, Z^2 denotes an acyl group having 2 to 11 carbon atoms with the proviso that Y^2 is an alkyl group having 4 to 11 carbon atoms; X^3 denotes a residual group of an aliphatic dibasic acid or an aromatic dibasic acid; and Y^3 and Z^3 each denote an alkyl group having 1 to 11 carbon atoms.

(9) A printed matter, characterized in that variable information is printed by an ink jet recording method on the receiving layer recited in any one of items (1) to (8).

(10) A method for producing the printed matter according to

any one of items (2) to (8), characterized by printing fixed information and then forming the receiving layer for an ink jet recording ink with a coater or a printer by an in-line system.

(11) A method for producing the printed matter according to
5 item (7) or item (8), characterized by providing the receiving layer for an ink jet recording ink with a coater or a printer by an in-line system on a printed surface still in a wet condition immediately after printing the fixed information with an oil-based ink.

(12) The method for producing a printed matter according to
10 item (10) or item (11), wherein the receiving layer for an ink jet recording ink is formed with a coater equipped with an anilox roll and a rubber roll.

Hereafter, the present invention will be described in more detail.

15 As the printing paper to be used in the printed matter of the present invention, general printing papers to which an ink can be printed well by various kinds of printing methods, typified by art paper, coated paper, cast-coated paper, luster paper, woodfree paper and medium-quality paper, can be used with no particular limitations.

20 As the method for printing fixed information in the present invention, a method of using conventional printers based on any printing method selected from the lithographic printing, relief printing and intaglio printing can be used. Moreover, as a printing ink, any of general oil-based ink, solvent-based ink and water-based ink can be
25 used. Especially, the lithographic printing and intaglio printing are the printing methods suitable for obtaining a beautiful printed matter, which is the object of the present invention, since these printing

methods can print minute images. Moreover, print patterns may be formed by a "selective printing" wherein no print image is formed in the area where images will be printed by the ink jet printing method afterwards.

5 Next, in the present invention, for forming a receiving layer for an ink jet recording ink (hereinafter referred simply to as "receiving layer") on the print surface of the printed matter obtained by the aforesaid printing methods, a coating agent which is obtained by dissolving or dispersing the following materials for constituting the
10 receiving layer in an aqueous medium and which can form a smooth receiving layer on the printed surface by coating or printing can be suitably used.

 As the resin for constituting the receiving layer, resins having a wetting function to water (ink-absorbing resins) and resins having a
15 function of fixing dyes or pigments in inks for ink jet recording (ink-fixing resins) are suitable. Examples of the former ink-absorbing resins are proteins such as casein and synthetic proteins, various kinds of starches such as oxidized starch and esterified starch, celluloses such as carboxymethyl cellulose and hydroxymethyl cellulose, polyvinyl
20 alcohols, polyvinyl acetals and polyvinylpyrrolidones. Examples of the latter ink-fixing resins are polyvinyl alcohols having a cationic group, acrylic resins having a cationic group and acrylamide resins having a cationic group.

 Furthermore, in order to improve the water resistance of the
25 receiving layer, it is also possible to incorporate aqueous polyurethane resins, aqueous polyester resins, epoxy resins, or the like.

 As a filler to be used for forming the receiving layer, inorganic

fillers such as silica, alumina sol, barium sulfate, calcium carbonate, clay and talc, and organic fillers such as polystyrene fine particles and polyethylene fine particles can be exemplified. The desirable form of the filler is a layered shape or a plate-like shape. Furthermore, porous
5 fillers are more desired.

As an aqueous medium, water or water admixed with a water-miscible organic solvent such as lower alcohols or various additives such as surfactant or antifoaming agent, as needed, can be used.

10 When the receiving layer is formed on the entire surface of a printed matter or on the printing ink film of the printed matter even in the case that the receiving layer is formed partially on the printed matter, the receiving layer preferably has a smooth continuous surface and preferably is as transparent as possible so as not to conceal printed
15 images. Furthermore, the receiving layer is preferably formed from a coating agent that does not dissolve the printing ink so that the printed surface would not cause blurring or bleeding. On the other hand, when forming a receiving layer only on the non-printed surface of the printed matter, any coating agent for forming a transparent receiving layer and
20 an opaque receiving layer can be used.

Moreover, the receiving layer may comprise either one layer, or two or more layers laminated. In the case of a receiving layer comprising a single layer, only an ink-absorbing resin, only an ink-fixing resin, or a mixture of the ink-absorbing and ink-fixing resins may be
25 used as the resin component of the layer. In the case of a receiving layer comprising two or more layers laminated, possible methods include a method wherein an lower layer where an importance is placed

on the adhesiveness to a printing paper or a print surface and an upper layer where an importance is placed on the ability to receive an ink jet recording ink are formed separately, and a method in which a function layer having the ability to absorb the liquid component of an ink jet recording ink and another function layer having the ability to fix the ink jet recording ink are formed separately. Particularly, it is desirable to use a receiving layer comprising an ink-absorbing resin as the lower layer and to use a receiving layer containing an ink-fixing resin as the upper layer, from the viewpoint that when an ink jet recording ink is printed, it is not blurred and a clear image is formed.


The content of the resin component and that of the filler in the receiving layer are desirably about 50 to 95% by weight for an ink-absorbing resin and/or an ink-fixing resin and about 5 to 50% by weight for the filler, based on the weight of the receiving layer after drying.

The coating amount of the receiving layer (the coating amount after drying, hereinafter the same) is not particularly limited. It is appropriately selected from the range of 1 to 30 g/m² for each layer both in the case of a receiving layer comprising one layer and in the case of a receiving layer comprising two or more layers.

Furthermore, in the present invention, especially in the case that fixed information is printed with an oil-based printing ink, when a coating agent having low contents of the aforesaid ink-absorbing resin, ink-fixing resin and filler is used, it is difficult to form a film from the coating agent on the oil-based ink film due to the low viscosity of the coating agent and repulsion between water and oil. On the other hand, when a coating agent having high contents of the aforesaid ingredients is used, the repulsion of the coating agent is reduced due to its high

viscosity but its application itself becomes difficult.

Then, for forming continuously a smooth receiving layer on a print film of an oil-based ink by using a low-viscosity coating agent which has easy application property, suitable methods include a method
5 using an acrylic resin for film forming obtained by emulsion polymerizing monomers containing 15% by weight or more of one or more of (meth)acrylic ester compounds with an alkyl group having 8 to 18 carbon atoms and a method using a film forming-improving agent represented by the following general formulas (1) to (3):



Here, X^1 denotes an alkylene group having 2 to 4 carbon atoms, Y^1 and Z^1 each denote an alkyl group having 1 to 4 carbon atoms,
15 and n denotes an integer of 1 to 4. X^2 denotes an alkylene group having 2 to 8 carbon atoms and Y^2 denotes H or an alkyl group having 1 to 11 carbon atoms. When Y^2 is H, Z^2 denotes an alkyl group having 4 to 11 carbon atoms or an acyl group having 4 to 11 carbon atoms. When Y^2 is an alkyl group having 1 to 3 carbon atoms, Z^2 denotes an acyl group
20 having 4 to 11 carbon atoms. When Y^2 is an alkyl group having 4 to 11 carbon atoms, Z^2 denotes an acyl group having 2 to 11 carbon atoms. X^3 denotes a residual group of an aliphatic dibasic acid or an aromatic dibasic acid, and Y^3 and Z^3 each denote an alkyl group having 1 to 11 carbon atoms.

25 Examples of the alkylene group having 2 to 4 carbon atoms represented by X^1 include an ethylene group, a trimethylene group, a propylene group, a tetramethylene group and a butylene group.

Examples of the alkylene group having 2 to 8 carbon atoms represented by X^2 include an ethylene group, a trimethylene group, a propylene group, a tetramethylene group, a butylene group, a pentamethylene group, a hexamethylene group, an octamethylene group and a 2-ethylhexylene group. Examples of the aliphatic dibasic acid that provides the residual group represented by X^3 include aliphatic dibasic acids having 4 to 10 carbon atoms such as succinic acid, adipic acid, azelaic acid and sebacic acid. Examples of the aromatic dibasic acid that provides the residual group represented by X^3 include phthalic acid, isophthalic acid and terephthalic acid. Examples of the alkyl group having 1 to 4 carbon atoms represented by Y^1 or Z^1 include a methyl group, an ethyl group, a propyl group, an isopropyl group, a butyl group, an isobutyl group and a sec-butyl group. Examples of the alkyl group having 1 to 11 carbon atoms represented by Y^2 include a methyl group, an ethyl group, a propyl group, an isopropyl group, a butyl group, an isobutyl group, a sec-butyl group, a pentyl group, a hexyl group, an octyl group, a 2-ethylhexyl group, a decyl group and an undecyl group. Examples of the alkyl group having 4 to 11 carbon atoms represented by Z^2 include a butyl group, an isobutyl group, a sec-butyl group, a pentyl group, a hexyl group, an octyl group, a 2-ethyl hexyl group, a decyl group and an undecyl group. Examples of the carboxylic acid that provides the acyl group having 2 to 11 carbon atoms represented by Z^2 include acetic acid, propionic acid, butyric acid, pentanoic acid, hexanoic acid octanoic acid, decanoic acid and an undecanoic acid. Examples of the alkyl group having 1 to 11 carbon atoms represented by Y^3 or Z^3 includes a methyl group, an ethyl group, a propyl group, an isopropyl group, a butyl group, an isobutyl group, a sec-butyl group, a

pentyl group, a hexyl group, an octyl group, a 2-ethylhexyl group, a decyl group and an undecyl group.

Examples of the (meth)acrylic ester compound with an alkyl group having 8 to 18 carbon atoms to be used for the synthesis of the aforesaid acrylic resins for film forming include n-octyl (meth)acrylate, 2-ethylhexyl (meth)acrylate, n-decyl (meth)acrylate, lauryl (meth)acrylate, stearyl (meth)acrylate. These may be copolymerized with (meth)acrylic ester compounds having 1 to 6 carbon atoms (for example, methyl (meth)acrylate, ethyl (meth)acrylate, propyl (meth)acrylate, butyl (meth)acrylate and hexyl (meth)acrylate), other acrylic monomers, styrenic monomers, and the like.

A coating layer comprising the aforesaid acrylic resin alone may be formed on a printing ink film, followed by further forming thereon a receiving layer containing an ink-absorbing resin and/or an ink-fixing resin, or a receiving layer in which the aforesaid acrylic resin is contained together with the ink-absorbing resin and/or the ink-fixing resin may be formed on the printing ink film. In the former case, it is desirable that the acrylic resin coating agent contains a filler. The coating amount of the coating agent (the coating amount after drying, hereinafter the same) is suitably selected from the range of 2 to 20 g/m². In the latter case, the acrylic resin is contained in the receiving layer adjoining the print film of an oil-based ink. Furthermore, in the case where an acrylic resin for film forming is used together with other resins, the content of the acrylic resin for film forming can be determined depending upon the relationship with the viscosity of the coating agent, or the like. However, in order to obtain a coating agent having a low viscosity and a good film forming property, it is desirable to satisfy the

following condition. That is, a good result is obtained when the proportion of the (meth)acrylic ester compound having an alkyl group having 8 to 18 carbon atoms used as a material for synthesizing the aforesaid acrylic resin is 15% by weight or more , based on all the resins
5 including the other resin used together.

Typical examples of the afore-mentioned film forming-improving agents are as follows. Examples of the compounds represented by the general formula (1) are dimethyl ether, diethyl ether or dibutyl ether of ethylene glycol, diethylene glycol or triethylene glycol;
10 dimethyl ether, diethyl ether or dibutyl ether of propylene glycol, dipropylene glycol or tripropylene glycol; dimethyl ether, diethyl ether or dibutyl ether of butylene glycol, dibutylene glycol or tributylene glycol. Examples of the compounds represented by the general formula (2) are monobutyl ether, monohexyl ether, monooctyl ether or monodecyl ether
15 of ethylene glycol, propylene glycol, butylene glycol or 2-ethylhexylene glycol, monobutyric ester, monohexanoic ester, monooctanoic ester or monodecanoic ester of ethylene glycol, propylene glycol, butylene glycol or 2-ethylhexylene glycol; ethylene glycol methyl ether butyrate, propylene glycol ethyl ether butyrate; ethylene glycol butyl ether acetate
20 and propylene glycol butyl ether butyrate. Examples of the compounds represented by the general formula (3) are dimethyl ester, diethyl ester or dibutyl ester of succinic acid, adipic acid or phthalic acid.

These film forming-improving agents can provide good effects when the film forming-improving agent is dissolved or mixed in an emulsion condition into a coating agent for forming a receiving layer in
25 an amount of about 1 to 8% by weight, optionally using a water-soluble organic co-solvent such alcohols or ketones having a low molecular

weight or the like, as needed.

As means for forming a receiving layer, various types of coaters such as a roll coater, a gravure coater, a flexocoater, a blade coater, a rod coater and an air knife coater can be used. Printing units
5 contained in printers used in the aforementioned various types of printing methods can also be used. A receiving layer may be formed over the entire surface of a printed matter, or may also be formed partially on the surface of the printed matter. When a gravure coater, a flexocoater or various printing methods are used, a receiving layer can
10 be formed partially. Moreover, the use of a flexo-style coating machine equipped with an anilox roll and a rubber roll is more desirable since such a machine can easily form a receiving layer having a large thickness.

Furthermore, the use of a coating agent that can form a
15 smooth receiving layer on the film of a printing ink even under the condition where the printing ink has not been fully dried is more suitable since the printing of the printing ink and the formation of the receiving layer can be performed at a series of processes (in-line method). Particularly, when fixed information is printed with an oil-based printing
20 ink, the formation of a coating for a receiving layer by the in-line method becomes still more difficult. However, by the use of the aforementioned film-forming acrylic resin or a film-forming-improving agent, a good receiving layer can be formed in the in-line method.

As such a method for forming a receiving layer in the in-line
25 method, a method in which the rear unit of a printing machine is used or a method in which a separate printer or coater is combined with the printing machine for the printing ink is employed. In addition, even a

method in which a receiving layer is formed afterwards by using a printer or a coater in a step different from a printing step (off-line method) can be used, there is no inconvenience at all.

In the present invention, when further printing variable
5 information, the information is printed by an ink jet recording method on the receiving layer provided in the previous step.

Although water-based inks are in the mainstream of ink jet recording ink, oil-based inks can also be used.

All steps including the printing of fixed information, the
10 formation of a receiving layer for an ink jet recording ink and the printing of variable information may be performed in the in-line method, if possible. However, all the steps may be conducted in the off-line method.

Furthermore, it is also possible to perform steps until the
15 formation of a receiving layer for an ink jet recording ink in a printing company and to perform the printing of variable information in a company other than the printing company.

In the case of a printed matter having variable information produced by the method of the present invention, a printing ink and an
20 ink jet recording ink do not contact directly to each other in the presence of the receiving layer. Therefore, even in the case of the combination of inks of different types such as an oil-based printing ink and a water-based ink for ink jet recording, neither repelling nor color irregularity is produced.

25 Furthermore, a substrate is satisfactory to have only printability to printing inks. Therefore, according to the present invention, beautiful printed matters having variable information can be

obtained more inexpensively and more simply, as compared with the existing methods in which a difficult technique, i.e. a compatibility between the printability to printing inks and printability to ink jet recording inks, is required.

5 Moreover, in the case of a printed matter having a receiving layer all over the printed surface thereof, an ink jet recording ink can be printed in arbitrary areas. On the other hand, a printed matter having a receiving layer partially is still more economically advantageous since it can save the amount of the coating agent to be used for forming the
10 receiving layer. Thus, much effects can be obtained.

BEST MODE FOR CARRYING OUT THE INVENTION

The present invention will be explained concretely by reference to Examples. However, the present invention is not limited to
15 these Examples, unless it deviates from its gist and application range. In the following description, "parts" denotes to "parts by weight".

1) Production of test offset printed matter

A test offset printed matter was obtained by printing a lithographic ink (Diatone Ecopure SOY GP-Yellow, manufactured by
20 Sakata Inx Corp.) to a coated paper (OK topcoat, manufactured by Oji Paper Co., Ltd.).

2) Preparation of coating agent for receiving layer and coating agent for film forming resin

Coating agents 1 to 3, 5 to 11 for forming a receiving layer
25 and coating agent 4 for film forming resin were prepared by charging predetermined amounts of materials according to the compositions (shown in parts by weight) given in Table 1, and then mixing with

stirring by use of a high-speed mixer.

3) Production of printed matters of Examples 1 to 21

Production of printed matters of Examples by in-line method

Printed matters of Examples 1 to 8 were obtained as follows:

5 Each of coating agents 1, 3, 5 to 9 and 11 for forming a receiving layer was applied by a double-coat coating method onto the ink-transferred surface of the test offset printed matter immediately after the printing, thereby forming a receiving layer. The coating amount of each receiving layer after drying was set to 4 g/m² (hereinafter the same).

10 A printed matter of Example 9 was obtained by applying coating agent 4 for film forming resin onto the ink-transferred surface of the test offset printed matter immediately after the printing, and then applying coating agent 2 for forming a receiving layer by a double-coat coating method, thereby forming a receiving layer. The coating amount
15 of the film forming resin layer after drying was set to 3 g/m².

A printed matter of Example 10 was obtained by applying coating agent 10 for forming a receiving layer by a double-coat coating method onto the surface of the receiving layer obtained in Example 2, thereby forming a further receiving layer.

20 A printed matter of Example 11 was obtained by applying coating agent 10 for forming a receiving layer by a double-coat coating method onto the surface of the receiving layer obtained in Example 9, thereby forming a further receiving layer.

Production of printed matters of Examples by off-line method

25 Printed matters of Examples 12 to 14 were obtained as follows: Each of coating agents 1, 2 and 10 for forming a receiving layer was applied by a double-coat coating method onto the ink-transferred

surface of the test offset printed matter dried for one day after the printing, thereby forming a receiving layer.

Printed matters of Examples 15 and 16 were obtained as follows: Coating agent 10 for forming a receiving layer was applied by a
5 double-coat coating method onto the surface of the receiving layer obtained in Example 12 or 13, thereby forming a receiving layer.

Production of printed matters having a receiving layer on a non-printed surface

Printed matters of Examples 17 to 19 were obtained as
10 follows: Each of coating agents 1, 2 and 10 for forming a receiving layer was applied by a double-coat coating method onto the non-ink-transferred surface of the test offset printed matter, thereby forming a receiving layer.

Printed matters of Examples 20 and 21 were obtained as
15 follows: Coating agent 10 for forming a receiving layer was applied by a double-coat coating method onto the surface of the receiving layer obtained in Example 17 or 18, thereby forming a further receiving layer.

In Examples 1 to 21, a flexocoater equipped with a 60 lines/cm anilox roll and a rubber roll was used for the application of the
20 coating agent for forming a receiving layer.

TABLE 1

Coating agent for forming receiving layer	1	2	3	4	5	6	7	8	9	10	11
Resin solution A ^{*1}	79.0	-	-	-	-	-	-	-	-	-	-
Resin solution B ^{*2}	-	79.0	40.0	-	-	77.0	77.0	77.0	77.0	-	-
Resin solution C ^{*3}	-	-	-	-	79.0	-	-	-	-	-	-
Resin solution D ^{*4}	-	-	-	-	-	-	-	-	-	79.0	40.0
Colloidal silica dispersion ^{*5}	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
Surfinol 104 ^{*6}	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Film forming resin ^{*7}	-	-	39.0	99.0	-	-	-	-	-	-	39.0
EGDE ^{*8}	-	-	-	-	-	2.0	-	-	-	-	-
EGM2EH ^{*9}	-	-	-	-	-	-	2.0	-	-	-	-
EGBAc ^{*10}	-	-	-	-	-	-	-	2.0	-	-	-
SuDM ^{*11}	-	-	-	-	-	-	-	-	2.0	-	-

- *1: 15 % by weight aqueous solution of polyvinyl alcohol having a polymerization degree of 1,700 and a hydrolysis degree of 88 % (the trade name : PVA 217, Kuraray Co., Ltd.)
- *2: 10 % by weight aqueous solution of polyvinyl alcohol obtained by
5 diluting resin solution A 1.5 times with water
- *3: 10 % by weight ethanol solution of a lauryltrimethylammonium salt of carboxymethyl cellulose (substitution degree of carboxymethyl group = 1.74)
- *4: 10 % by weight aqueous solution of cation-modified polyvinyl alcohol
10 (Gosenol K-210, The Nippon Synthetic Chemical Industry Co., Ltd.)
- *5: 40 % by weight aqueous dispersion of Snowtex OL (manufactured by Nissan Chemical Industries, Ltd.)
- *6: Surfactant of acetylene glycol type manufactured by Air Products and Chemicals, Inc.
- 15 *7: Acrylic resin emulsion containing 30 % by weight of solids obtained by a usual emulsion-polymerization method from a monomer mixture of n-octyl methacrylate/butyl acrylate/methyl methacrylate/styrene = 25/15/30/30 by weight
- *8: Ethylene glycol diethyl ether
- 20 *9: Ethylene glycol mono 2-ethylhexyl ether
- *10: Ethylene glycol butyl ether acetate
- *11: Dimethyl succinate

COMPARATIVE EXAMPLES

- 25 The test offset printed matter immediately after the printing having no receiving layer, the printed matter dried for one day after the printing, and the coated paper having no print were used as

Comparative Examples 1, 2 and 3, respectively.

4) Printing of ink jet recording ink

About 0.3mm-wide thin lines of an indigo blue monochromic color and about 3 mm-wide thick lines of an indigo blue monochromic color and a full-color portrait image were printed with a commercially available ink jet printer (MJ-830C, piezo type, manufactured by Seiko Epson Corp., using a water-based ink) to each of the receiving layers of Examples 1 to 21, the print surfaces of Comparative Examples 1 and 2 and the surface of the paper of Comparative Example 3.

5) Evaluation

(1) Evaluation of thin line

Sharpness of line

The condition of the thin lines formed by printing the ink jet recording ink was observed visually. Sharpness of the printed matters was evaluated on the basis of the presence of blurring or repelling according to the criteria that the spreading of a line twice or more in width is "blurring" and that a discontinuous thin line is "repelling".

A : There is no blurring or repelling.

B : There is blurring or repelling.

Fixing property

The fixing property was evaluated on the basis of the presence of smearing or fading after rubbing the printed surface with a spatula immediately after the printing.

A: There was no smearing or fading.

B: There was a little smearing or fading but the thin line was kept in its original condition.

C: There was severe smearing or fading and the line did not keep its

original condition.

(2) Evaluation of portrait image

Muddiness

5 The portrait images obtained were observed visually. An image having the color tones which the inks originally have is evaluated as "there is no muddiness", and that having muddy color tone is evaluated as "there is a muddiness." In Comparative Examples 1 and 2, severe repelling prevented evaluation.

A: There was no muddiness.

10 B: There was muddiness.

(3) Evaluation of drying property

15 The drying property was evaluated on the basis of the time taken until a filter paper no longer gets colored even when the filter paper is placed on the thick lines and a load of 6,000 Pa is applied on the filter paper after a predetermined period from the time immediately after the printing of the thick lines.

A: The thick lines get dried within 2 minutes after the printing.

B: The thick lines get dried after 2 minutes but within 5 minutes from the printing.

20 C: The thick lines do not get dried within 5 minutes after the printing.

TABLE 2

	Example																				Com.Ex.			
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	1	2	3
Layer construction																								
(1) Coating agent	-	-	-	-	-	-	-	-	4	-	4	-	-	-	-	-	-	-	-	-	-	-	-	-
(2) Coating agent	1	3	5	6	7	8	9	11	2	3	2	1	2	10	1	2	1	2	10	1	2	-	-	-
(3) Coating agent	-	-	-	-	-	-	-	-	-	10	10	-	-	-	10	10	-	-	-	10	10	-	-	-
Performance																								
Sharpness	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	B	B	B
Fixing property	B	B	B	B	B	B	B	B	B	A	A	B	B	A	A	A	B	B	A	A	A	C	C	B
Muddiness	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	-	-	B
Drying property	B	B	A	A	A	A	A	B	A	A	A	A	A	B	A	A	A	A	B	A	A	C	C	C

(1) Coating agent: coating agent for a film forming resin

(2) Coating agent: coating agent for forming a receiving layer which is the first layer from the print surface (the second layer in Examples 9 and 11)

(3) Coating agent: coating agent for forming a receiving layer which is the second layer from the print surface (the third layer in Example 11)

As described above with reference to Examples and Comparative Examples, the printed matter of the present invention is one in which usually used printing paper is employed as a substrate but beautiful images of fixed information and variable information can be
5 formed economically and efficiently by using both printing method and ink jet recording method.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
222